

Specifications

Part number 701960-6WS241
 Dimensions L x W x H 24.0" x 0.3" x 0.1"
 Viewing angle 120°
 LEDs per section 3
 Color temperature (nominal) 6500 K
 Min. radial bend radius 1"
 Operating temperature -40° C to +70° C
 Special features "Snap-n-Stretch" 1.7" sections
 for easy flat bends and connections
 Power 0.3 W per section, 4.2 W per strip
 Long 14.0 W
 Efficacy 85 lm/W
 Fastening Peel-n-stick
 Packaging 12 strips per box
 Lumens per strip 365



BendLUX is covered by patents pending.

Power Supply Capacity

12 VDC power supply	BendLUX
20 W Power Supply	8 ft
60 W Power Supply	25 ft
2 x 60 W Power supply	2 x 25 ft
Watts per foot	2.1 W

Recommended Coverage Chart

Depth	Mods/ft	Max. stroke coverage per row		Inches on center dark vinyl	Inches on center perforated vinyl
		Single row	Multiple rows		
1.2"	7	1.2"	N/A	Test	Test

These guidelines are intended to provide only an approximation of BendLUX product required for your sign, assuming an optimal balance of performance and cost. SloanLED is not responsible for the actual results based on the use of these guidelines.

Notes:

- It is recommended that you first test LED density in sample letter/cabinet to evaluate brightness, uniformity and color
- Should you have questions or require assistance in testing, please contact your SloanLED customer service representative
- For multiple rows, start 3" from return
- Products can be used in can depths deeper or shallower than listed above, but testing is recommended
- Acrylic material used for all testing was 0.1875" thickness sign grade 7328 acrylic for White LEDs



principalsloan.com
 325.227.4577
 3490 Venture Dr., San Angelo, TX 76905