

FLEXIBRITE WIDE G2

Flexible LED illumination



Specifications

Dimensions L x W x H 24" x 0.87" x 1.26"

Input 24 V

Min. bend radius 8"

Power 2.01W/ft

Operating temperature -40° C to +65° C

Environment IP67

Power supply 24V

Run footage Max. 45.9'

Connection wire Available every 9.84"

Warranty 5-year Product / 5-year Labor

Multiple applications including:

- Neon tube light source
- Building and sign outline lighting
- General and cove lighting

New and improved design features convenient connection wires for faster, easier installation



Dual-color silicone extrusion

Bends front-to-back with 8" radius

UV-resistant

Product Options


Length	CCT/color	Jacket color	Lm/ft	Cut section length	Assemblies/100W PS	W/assembly	Part number
24-ft	6500 K	White	200	4"	1.0	48.2	M-WW024-65
	Red (630 nm)	Red	18				M-WW024-RD
	Green (522 nm)	Green	40				M-WW024-GR
	Blue (468 nm)	Blue	11				M-WW024-BL



IMPORTANT WARRANTY INFO


NOTE: The LED neon itself and all its components may not be mechanically stressed. Please ensure that the power supply is adequate to operate the total load. Only qualified personnel should be allowed to perform installations. The design of the housing should be according to the IP standards in the application. If surge protection structure not within power supplier, a lightning protector should be needed additionally. Before cutting and sealing, please read the user manual, and please ensure you have read and fully understand it. Please do not twist the product and do not bend it in wrong direction.

Bend Direction




FlexiBRITE Wide G2
only bends as shown above.

Also Available



FlexiBRITE Back-Bend G2
only bends as shown above.




FlexiBRITE Side-Bend G2
only bends as shown above.

FLEXIBRITE WIDE G2


Flexible LED illumination





Accessories



A-WW-TRAL-3
3.28-ft Aluminum mill finish
extrusion for outdoor applications.



A-WW-CHSS
Stainless steel chain
for curve installation.




M-WW-PCLIP
Transparent PC mounting clip*

* Transparent clips are not warranted
if used in outdoor applications.

End Caps


End cap quantities are available upon request.





A-WW-ECKIT
Silicone end cap kit.
Includes silicone glue, ten (10) end caps and ten (10) inserts.

Wiring

Single color product.



Dimensions



(Distance between connection wires)

pindustries.com

325.227.4577

3490 Venture Dr., San Angelo, TX 76905