

# Plastic Universal 60W Power Supply HE



## PART

SKU

P-OH060-12-PL-P-HE

## FEATURES

- Economical
- Smaller footprint
- Easy to ground
- Load to 100% of capacity
- Multi-volt 100-277 VAC

## PERFORMANCE

Input Voltage	90~305 VAC
Input Current	0.97A~0.55A
Input Frequency	47~63Hz
Power Factor	Normal
Output Voltage	DC12V ±3%
Output Current	0-5.0A
Output Power	60W Max.

## SAFETY

Over Current Protection	115~140%
Short Circuit Protection	Hiccup mode, auto recover
Other Protection	Over Voltage/Over Load/Short Circuit
UL	UL879 / UL8750
CE-LVD	EN61347-1:2008+A1:2011+A2:2013 EN61347-2-13:2014

## PHYSICAL

Length	6.71" (170.5mm)
Width	1.65" (42mm)
Height	1.38" (35mm)
Mounting Length*	6.75" (171.45mm)
Weight	0.73lbs (330g)
Lead Lengths	7" (177.8mm)

## ENVIRONMENTAL

CE-EMC	EN55015, EN61527, EN61000
FCC	FCC 47 CFR PART 15, CLASS B
IP Rating	1P67
Operating Temperature	-30°C to 60°C (-22°F to 140°F)
Storage Temperature	-40°C to 85°C (-40°F to 185°F)
Relative Humidity	20 to ±90% RH non cond.

\*NOTE: To avoid breaking the mounting tabs, #4 size are required



www.p-led.com • 325-227-4577 • sales@p-led.com



\*\*\*5 year product / 5 year labor warranty applicable for this unit if used with a Qwik Box.

Data subject to changes. **REV20230503**