

# LEDBLADE

LED canopy fascia and wall wash fixture

**24**  
VDC

## Specifications

Part number ..... 701994-6WA5X1  
 Dimensions L x W x H ..... 58.6" x 1.0" x 1.0"  
 LEDs per assembly ..... 72  
 Operating temp. .... -40° C to +70° C  
 Life rating ..... L<sub>70</sub> @ >60,000 hours  
 Power per assembly ..... 30 W  
 Optional dimming ..... PWM  
 Efficacy ..... 120 lm/W  
 Ingress protection ..... IP66  
 UL location rating ..... Dry, damp, and wet  
 Fastening ..... Mounting clips  
 Packaging ..... Twelve (12) assemblies per box  
 Color temperature ..... 6500 K  
 Lumens per assembly ..... 3,118



## Power Supply Capacity

24 VDC power supply	Loading
60 W Power Supply	One (1), 5-ft LEDBlade section
100 W Power Supply	Three (3), 5-ft LEDBlade sections
300 W Power Supply	3 x three (3), 5-ft LEDBlade sections
Power used per foot in Watts	5.31 W

## Accessories

Accessory	Part number	Description
<b>Cables and connectors</b>		
701158-120-DC & 701158-180	701187-DC	701188-DC
Hook-up cable, 10-ft	701158-120-DC	Connects LEDBlade to power supply
Hook-up cable, 15-ft	701158-180	
Wiring pigtail, large connector	701187-DC	Male, outdoor-rated connector
Wiring pigtail, small connector	701188-DC	Female, outdoor-rated connector
<b>Mounting</b>		
Mounting clip	402453	For mounting product to surfaces
Field end cap	402494	For adjusting product length
Field end cap installation kit	701491	Glue, PCB sealer, de-burr sandpaper, instructions



principalsloan.com  
 325.227.4577  
 3490 Venture Dr., San Angelo, TX 76905

