



LIGHT TAPE

Versatile, economical, and reliable light tape from Principal LED.

From accent cove lighting, edge-lit acrylic, thin channel letters, and box lighting, Principal LED has you covered with our superior quality LED light tape. We offer over 25 different light tape styles and colors to choose from for endless creative opportunities. Backed by a 5-year warranty and leading technology.



LIGHT TAPE
STANDARD

 **PRINCIPAL LED**
WE SPEAK SIGN LANGUAGE

 **QWIK**
CONNECT
SYSTEM.
S² Technology™ Simple • Secure • Solderless

Light Tape Series

- Excellent price-per-lumen value
- Wide range of color options including RGB
- Two brightness level styles
- Available in potted (outdoor, IP67) and non-potted (indoor, IP65) designs
- UL and cUL recognized (SAM Manual), CE, CSA, RoHs
- Accessories: Middle connector and jumper connector



Scan this QR Code with your smart phone to visit our website for detailed specs.

Light Tape 300

300 LEDs per 16.4 ft. (5m) reel (150 LEDs for RGB)

	RGB	Red	Amber	Green	Blue	Warm White	Medium White	Pure White
Intensity (LM/ft.)	N/A	33	35	52	14	125	150	150
Efficacy (LM/W)	N/A	22	23	35	9	83	100	100
Power (W/ft.)	1.8	1.5	1.5	1.5	1.5	1.5	1.5	1.5
Wavelength	varies	625nm	592nm	525nm	460nm	3100K	4300K	6300K

Light Tape 600

600 LEDs per 16.4 ft. (5m) reel (300 LEDs RGB x2)

	RGB x2	Red x2	Warm White x2	Med. White x2	Pure White x2
Intensity (LM/ft.)	N/A	66	250	300	300
Efficacy (LM/W)	N/A	22	83	100	100
Power (W/ft.)	3.5	3.0	3.0	3.0	3.0
Wavelength	varies	625nm	3100K	4300K	6300K

Qwik Connect™ Tape

- Save time with S3 Technology: “Safe, secure, and solderless” patent-pending micro-rivet system
- Easily match with Street Fighter modules using the same chip
- Allows for on-site fabrication
- UL and cUL recognized (SAM Manual), CE, RoHs
- IP33 protection grade, 120° high dome lambertian beam angle
- Accessories: Qwik connect crimper, jumper, whips



Scan this QR Code with your smart phone to visit our website for detailed specs.

	Prime	Prime HD	Punch
Intensity (LM/ft.)	175 LM/ft.	350 LM/ft.	365 LM/ft.
Efficacy (LM/W)	117 LM/W	117 LM/W	91 LM/W
Power (W/ft.)	1.5 W/ft.	3.0 W/ft.	4.0 W/ft.
Packaging	164 ft. (50m) reel	164 ft. (50m) reel	15 ft. reel