

HanleyLED

# NRG 2 PRO

24  
VDC


24V LED illumination for small channel letters



## Specifications

- Beam angle ..... 170° High efficiency optics
- Power (W)..... 0.62 W/mod (1.09 W/ft)
- Efficacy..... 170 lm/W
- Modules/ft..... 1.77/ft (fully-stretched)
- Environment ..... IP68 waterproof
- Operating temp. .... -40° C to +60° C
- Storage temp. .... -40° C to +70° C
- Cascade..... 80 mods single-ended power feed  
160 mods double-ended power feed
- Packaging..... Anti-static bag, 80 modules (45 ft)/bag,  
7 bags/inner carton, 14 bags/outer carton
- Warranty..... 10-Year Product/5-Year Limited Labor

Better spacing with High Efficiency NRG Lens




Less labor installing less modules and power supplies

## Product Options

SKU	CCT/Color	Lumens
HLED-PN2W7K	7000 K	105 lm/mod (185 lm/ft)
HLED-PN2W65K	6500 K	
HLED-PN2W5K	5000 K	
HLED-PN2W4K	4000 K	
HLED-PN2W32K	3200 K	
HLED-PN2RED	Red (620-625 nm)	34 lm/mod (60.2 lm/ft)
HLED-PN2BLUE	Blue (460-470 nm)	9.3 lm/mod (16.4 lm/ft)


## Light Distribution



## Power Supply Options

Product	35 W, 24V	60 W, 24V	96 W, 24V	100 W, 24V	150 W, 24V	240 W, 24V	288 W, 24V
NRG 2 Pro	56 mods	96 mods	154 mods	161 mods	240 mods	384 mods	462 mods

## Dimensions



principalsloan.com  
325.227.4577  
3490 Venture Dr., San Angelo, TX 76905

