

PINNACLE™ HE 24V

24V LED channel letter illumination

24
VDC



Specifications

- SKU 6500 K..... M-SFT04-65-24
5000 K..... M-SFT04-50-24
- UL part number PL-OP1-TO4-P
- Dimensions L x W x H 4.05" x 0.69" x 0.3"
- Beam angle 170° Diamondback optic lens
- Module on-center spacing 10.91"
- Color temperatures..... 6500 K, 5000 K
- Intensity 227 lm/mod (250 lm/ft)
- Efficacy..... 172 lm/W
- Mounting options Peel & Stick and mechanical screw hole
- Operating temp. -40° C to +60° C
- Environment IP67
- Power supply..... 24 VDC
- Max. mods in series..... 36 mods (37.73 ft)
- Max. mods per power supply... 72
- Wire color White (+), Gray (-)
- Power (W)..... 1.32 W/mod (1.45 W/ft)
- Packaging Mods per bag: 72 (65.45 ft)
Mods per case: 1008 (916.36 ft)
- Bag color..... Green
- Warranty 10-Year Product / 5-Year Limited Labor



Pairs well with **VersaStik**



Recommended coverage chart

Depth	Mods/ft	Max stroke	Multi-row on-center spacing
5-12"	1.1	18" (single row)	15"

Product and depth may vary depending on face material and desired brightness. All spacing guidelines in this chart were done using 7328 White Acrylic faces. Other materials, thicknesses, and color can affect these guidelines in your sign. To ensure accuracy, it is recommended that you test the product in your specific application in a dark setting prior to installation. If you have concerns or questions about the materials you are using for your application please contact us for assistance.

Power Supply Options

Product	20 W		60 W		100 W	
	Watts/Mod	Max. Mods	Watts/Mod	Max. Mods	Watts/Mod	Max. Mods
Pinnacle HE 24V	1.32	15	1.32	45	1.32	72

* Watts per mod may vary depending on run footage.



principalsloan.com
325.227.4577
3490 Venture Dr., San Angelo, TX 76905

