

POSTERBOX 3

24
VDC

Large, shallow fabric-faced light box illumination



Specifications

SKU	Short	701946-6WSRP1
	Long	701946-6WLRP1
Dimensions L x W x H	Short	98.9" x 1.50" x 0.74"
	Long	19.73" x 1.50" x 0.74"
Viewing angle	12.2° x 44.8° illumination	
LEDs per assembly	Short	3
	Long	6
Color temperature (nominal)	6500 K	
Min. cabinet depth	Single-sided	3"
	Double-sided	4"
Operating temperature	-40° C to +70° C	
Protection class	IP66	
Life rating	>60,000 hours	
Power per module	Short	7.2 W
	Long	14.0 W
Efficacy	Short	118 lm/W
	Long	121 lm/W
Fastening	Mechanical fasteners, Peel-n-stick (optional)	
Packaging	6 assemblies per tray, 5 trays per carton	
Lumens per assembly	Short	850
	Long	1700



Power Supply Capacity*

	PosterBOX 3 Short	PosterBOX 3 Long
24 VDC power supply	Maximum units per power supply*	
60 W Power Supply	7	3
100 W Power Supply	12	6
300 W Power Supply	3 x 12	3 x 6
Watts per assembly	7.2	14.0

* Combination of units must not exceed maximum power supply output.

The PosterBOX™ product family is licensed by Signify (formerly Philips Lighting) in relation to the following patents:
 North America: US7841733. Europe: EP1938298, NL1030161, NL2000273, DE202006020673.6. Asia: CN101300616.
 PosterBOX products are licensed under Signify's EnabLED program when bought as a PosterBOX lighting kit solution including a SloanLED power supply. Final application in which PosterBOX lighting kit solution is installed is covered by SloanLED's licensing agreement with Signify and free from any further royalties relating to the patents listed above.



principalsloan.com
 325.227.4577
 3490 Venture Dr., San Angelo, TX 76905

