POSTERBOX 3

24 VDC

Large, shallow fabric-faced light box illumination

PosterBOX Series

Specifications

SKU ..... Short 701946-6WSRP1
Long 701946-6WLRP1

Dimensions L × W × H ..... Short ..... 9.89" × 1.50" × 0.74"
Long ..... 19.73" × 1.50" × 0.74"

Viewing angle ..... 12.2° × 44.8° illumination

LEDs per assembly ..... Short 3
Long 6

Color temperature (nominal) ..... 6500 K

Min. cabinet depth ..... Single-sided ..... 3"
Double-sided ..... 4"

Operating temperature ..... -40° C to +70° C

Protection class IP66

Life rating ..... >60,000 hours

Power per module ..... Short ..... 7.2 W
Long ..... 14.0 W

Efficacy ..... Short ..... 118 lm/W
Long ..... 121 lm/W

Fastening ..... Mechanical fasteners, Peel-n-stick (optional)

Packaging ..... 6 assemblies per tray, 5 trays per carton

Lumens per assembly ..... Short 850
Long 1700

RoHS Compliant

Power Supply Capacity*

24 VDC power supply	PosterBOX 3 Short	PosterBOX 3 Long
	Maximum units per power supply*	
60 W Power Supply	7	3
100 W Power Supply	12	6
300 W Power Supply	3 × 12	3 × 6
Watts per assembly	7.2	14.0

* Combination of units must not exceed maximum power supply output.

The PosterBOX™ product family is licensed by Signify (formally Philips Lighting) in relation to the following patents: North America: US7841733. Europe: EP1938298, NL1030161, NL2000273, DE202006020673.6. Asia: CN101300616. PosterBOX products are licensed under Signify's EnabLED program when bought as a PosterBOX lighting kit solution including a SloanLED power supply. Final application in which PosterBOX lighting kit solution is installed is covered by SloanLED's licensing agreement with Signify and free from any further royalties relating to the patents listed above.

10 YEAR Product & Labor WARRANTY

principalsloan.com
325.227.4577
3490 Venture Dr., San Angelo, TX 76905

© 2025 Principal Industries Rev B 2025-02-12 Specifications subject to change without notice.

PRINCIPAL SLOAN
A Principal Industries Company