

QWIK MOD™ 24V 24 VDC

24V LED channel letter illumination



Specifications

- SKU M-QMDX2-71
- UL number PL-QM2-TW150-P
- Dimensions L x W x H 2.2" x 0.69" x 0.25"
- Beam angle 170° Ultra-wide low-dome batwing optic with Diamondback Optic Lens Technology
- Mods per ft 1.7
- Color temperature 7100 K
- Intensity 94.1 lm/mod (160 lm/ft)
- Efficacy 118 lm/W
- Mounting options Peel-N-Stick and mechanical
- Operating temp. -30° C to +60° C
- Environment IP68
- Packaging Mods per bag: 76 (44.7 ft)
..... Mods per case: 912 (536.52 ft)
- Power supply 24 VDC
- Wire color White (+), Gray (-)*
- Warranty 10-Year Product / 5-Year Limited Labor



Power Supply Options

Product	60 W		100 W	
	Watts/Mod	Max. Mods	Watts/Mod	Max. Mods
Qwik Mod 2	0.8	76	0.81	120

* Check module for polarity.

* Watts per mod may vary depending on run footage.



Recommended coverage chart

Model	CCT	Depth	Mods/ft	Single stroke width	Multi-row on-center spacing
Qwik Mod 2	7100 K	3"	1.7	8"	7"
		4"		12"	12"
		5"		16"	13"
		6"		18"	14"

Product and depth may vary depending on face material and desired brightness. All spacing guidelines in this chart were done using 7328 White Acrylic faces. Other materials, thicknesses, and color can affect these guidelines in your sign. To ensure accuracy, it is recommended that you test the product in your specific application in a dark setting prior to installation. If you have concerns or questions about the materials you are using for your application please contact us for assistance.



principalsloan.com
325.227.4577
3490 Venture Dr., San Angelo, TX 76905

