QWIK MOD™ 24V G1 24 VDC

24V LED channel letter illumination

QWIKMOD Series

Specifications

SKU M-QMDX2-71

UL number PL-QM2-TW150-P

Dimensions L × W × H ..... 2.2" × 0.69" × 0.25"

Beam angle ..... 170° Ultra-wide low-dome batwing optic with Diamondback Optic Lens Technology

Mods per ft 1.7

Color temperature ..... 7100 K

Intensity ..... 94.1 lm/mod (160 lm/ft)

Efficacy ..... 118 lm/W

Mounting options ..... Peel-N-Stick and mechanical

Operating temp. ..... -30° C to +60° C

Environment IP68

Packaging ..... Mods per bag: 76 (44.7 ft)
Mods per case: 912 (536.52 ft)

Power supply ..... 24 VDC

Wire color ..... White (+), Gray (-)*

Warranty ..... 10-Year Product / 5-Year Limited Labor

* Check module for polarity.

Power Supply Options

Product	60 W		100 W	
	Watts/Mod	Max. Mods	Watts/Mod	Max. Mods
Qwik Mod 2	0.8	76	0.81	120

* Wattts per mod may vary depending on run footage.

E341517

RoHS Compliant

Recommended coverage chart

Model	CCT	Depth	Mods/ft	Single stroke width	Multi-row on-center spacing
Qwik Mod 2	7100 K	3"	3	8"	7"
		4"	1.7	12"	12"
		5"		16"	13"
		6"		18"	14"

Product and depth may vary depending on face material and desired brightness.
All spacing guidelines in this chart were done using 7328 White Acrylic faces. Other materials, thicknesses, and color can affect these guidelines in your sign. To ensure accuracy, it is recommended that you test the product in your specific application in a dark setting prior to installation. If you have concerns or questions about the materials you are using for your application please contact us for assistance.

10|5 YEAR
10-Year Product | 5-Year Labor
WARRANTY



"Ultra-Wide" Low-Dome Batwing Optic

principalsloan.com
325.227.4577
3490 Venture Dr., San Angelo, TX 76905

© 2026 Principal Industries Rev A 2026-02-24

Specifications subject to change without notice.

PRINCIPAL SLOAN
A Principal Industries Company