

STREET WRAP™ FLEX BACK-BEND (NON-RGB)

Flexible LED illumination

24
VDC



Specifications

Dimensions L x W x H 24-ft and custom lengths available

Min. bend radius 2.36"

Power 3.66 W/ft.

Run footage Max. 24 ft.

Applications Neon tube light source, building and sign outline lighting and cover lighting, indoor/outdoor, cursive letters and design


Operating temp. -40° C to +65° C

IP rating IP67

Voltage 24 V

Power supply Principal Sloan 24V

Warranty 5-year Product/5-year Labor



* Custom colors will utilize white LEDs behind a color matched silicone over molding and the MOQ is 656.168 ft.



Product Options

CCT/color	Jacket color	Lm/ft	Cut section length	Max. length/ 96 W PS	W/max. length	SKU
6500 K	White	305	3.9370"	287.4016"	87.7	M-SX024-65
5000 K						M-SX024-50
4000 K						M-SX024-40
Red (623 nm)	Red	25				M-SX024-RD
Orange (609 nm)	Orange	116				M-SX024-OR
Yellow (590 nm)	Yellow	158				M-SX024-YL
Green (525 nm)	Green	42				M-SX024-GR
Blue (468 nm)	Blue	15				M-SX024-BL

IMPORTANT WARRANTY INFO

This warranty is void if any cuts are made in the field.

Any cuts must be made by Principal Sloan to maintain warranty.

NOTE: The LED neon itself and all its components may not be mechanically stressed. Please ensure that the power supply is adequate to operate the total load. Only qualified personnel should be allowed to perform installations. The design of the housing should be according to the IP standards in the application. If surge protection structure not within power supplier, a lightning protector should be needed additionally. Before cutting and sealing, please read the user manual, and please ensure you have read and fully understand it. Please do not twist the product and do not bend it in wrong direction, see Figure 1 for a correct demonstration.


STREET WRAP™ FLEX BACK-BEND (NON-RGB)

24
VDC

Flexible LED illumination





Accessories




Transparent PC clips*
A-SXMH-CLPL

* Transparent clips are not warranted if used in outdoor applications.



4-ft & 8-ft Aluminum mill finish extrusion for outdoor applications

4-ft: A-SXMH-TRAL-4
8-ft: A-SXMH-TRAL-8



Aluminum mill finish clips for outdoor applications
A-SXMH-CLAL




End Caps*



Silicone end cap
A-SXHW-ECSI


* End cap quantities are available upon request.




Silicone insert, single color
X-C-SX-SI1C



Silicone glue
A-SWFX-SA




Silicone insert, RGB
X-C-SX-SI3C



Wiring

Single color product



Types of Feed




Bottom feed

Top view




Bottom feed

Front view



End feed

Top view



End feed

Front view

principalsloan.com
325.227.4577
3490 Venture Dr., San Angelo, TX 76905

