

STREET WRAP™ FLEX SIDE-BEND RGB


24
VDC

Flexible LED illumination



Specifications

- Dimensions L x W x H 24-ft and custom lengths available
- Min. bend radius 2.36"
- Power 3.66 W/ft.
- Run footage Max. 24 ft.
- Applications Neon tube light source, building and sign outline lighting and cover lighting, indoor/outdoor, cursive letters and design
- Operating temp. -40° C to +65° C
- IP rating IP67
- Voltage 24 V
- Power supply Principal Sloan 24V
- Warranty 5-year Product/5-year Labor




Product Options



CCT/color	Jacket color	Lm/ft	Cut section length	Max. length/ 96 W PS	W/max. length	SKU
RGB*	White	N/A	3.2795"	287.5591"	87.7	M-SV024-3C

* All RGB/ RGBW opportunities will only utilize Principal Sloan Superior Series Class 2 Power Supplies.

Wiring



IMPORTANT WARRANTY INFO

This warranty is void if any cuts are made in the field. Any cuts must be made by Principal Sloan to maintain warranty.
NOTE: The LED neon itself and all its components may not be mechanically stressed. Please ensure that the power supply is adequate to operate the total load. Only qualified personnel should be allowed to perform installations. The design of the housing should be according to the IP standards in the application. If surge protection structure not within power supplier, a lightning protector should be needed additionally. Before cutting and sealing, please read the user manual, and please ensure you have read and fully understand it. Please do not twist the product and do not bend it in wrong direction, see Figure 2 for a correct demonstration.


STREET WRAP™ FLEX SIDE-BEND RGB

24
VDC

Flexible LED illumination




Accessories




Transparent PC clips*
A-SVMH-CLPL

* Transparent clips are not warranted if used in outdoor applications.




4-ft & 8-ft Aluminum mill finish extrusion for outdoor applications

4-ft: A-SVMH-TRAL-4
8-ft: A-SVMH-TRAL-8



Aluminum mill finish clips for outdoor applications

A-SVMH-CLAL



Stainless steel chain for curve installation


A-SVMH-CHSS

End Caps*



Silicone end cap
A-SVHW-ECSI

* End cap quantities are available upon request.





Silicone insert, single color
X-C-SV-S1C


Silicone insert, RGB
X-C-SV-S13C



Silicone glue
A-SWFX-SA




Types of Feed




Bottom feed right

Top view




Bottom feed right

Front view




Bottom feed left

Top view




Bottom feed left

Side view



End feed

Top view



End feed

Side view

principalsloan.com
325.227.4577
3490 Venture Dr., San Angelo, TX 76905

