

STREET WRAP™ FLEX WIDE 24 VDC

Flexible LED illumination



FLEX

Specifications

Dimensions L x W x H See table x 1.26" x 0.71"
 Input 24 V
 Min. bend radius 8"
 Power 2.00 W/ft.
 Operating temp. -40° C to +65° C
 Environment IP67
 Power supply Principal Sloan 24V
 Warranty 5-year Product/5-year Labor



Product Options

CCT/color	Jacket color	Lm/ft	Cut section length	Max. length/ 96 W PS	W/max. length	SKU
6500 K	White	88	3.9370"	562.9921"	93.8	M-TD047-65
Red (623 nm)	Red	24				M-TD047-RD
Green (525 nm)	Green	8	2.8110"	562.2047"		M-TD047-GR
Blue (468 nm)	Blue	25				M-TD047-BL
Cyan	White	11		90.8	M-TD047-CN	
Pink		6		92.8	M-TD047-PK	
RGB		N/A	93.8	M-TD047-3C		

Accessories



8-ft aluminum track
A-TD-TRAL-8

IMPORTANT WARRANTY INFO

This warranty is void if any cuts are made in the field. Any cuts must be made by Principal Sloan to maintain warranty. **NOTE:** The LED neon itself and all its components may not be mechanically stressed. Please ensure that the power supply is adequate to operate the total load. Only qualified personnel should be allowed to perform installations. The design of the housing should be according to the IP standards in the application. If surge protection structure not within power supplier, a lightning protector should be needed additionally. Before cutting and sealing, please read the user manual, and please ensure you have read and fully understand it. Please do not twist the product and do not bend it in wrong direction, see Figure 2 for a correct demonstration.

principalsloan.com
 325.227.4577
 3490 Venture Dr., San Angelo, TX 76905

