

STREET WRAP™ FLEX WIDE (NON-RGB)

Flexible LED illumination

24
VDC



Specifications

Dimensions L x W x H See table x 1.26" x 0.71"
Min. bend radius 8"
Power 2.00 W/ft.
Operating temp. -40° C to +65° C
IP rating IP67
Voltage 24 V
Power supply Principal Sloan 24V
Warranty 5-year Product/5-year Labor



**Dual extrusion,
diffused, UV-resistant
silicone lens and thermal
conductive base**

Product Options

CCT/color	Jacket color	Lm/ft	Cut section length	Max. length/ 96 W PS	W/max. length	SKU
6500 K	White	200	3.9370"	562.9921"	93.8	M-TD047-65
Red (623 nm)	Red	24				M-TD047-RD
Green (525 nm)	Green	40	2.8110"	562.2047"	93.7	M-TD047-GR
Blue (468 nm)	Blue	11				M-TD047-BL



IMPORTANT WARRANTY INFO

This warranty is void if any cuts are made in the field.

Any cuts must be made by Principal Sloan to maintain warranty.

NOTE: The LED neon itself and all its components may not be mechanically stressed. Please ensure that the power supply is adequate to operate the total load. Only qualified personnel should be allowed to perform installations. The design of the housing should be according to the IP standards in the application. If surge protection structure not within power supplier, a lightning protector should be needed additionally. Before cutting and sealing, please read the user manual, and please ensure you have read and fully understand it. Please do not twist the product and do not bend it in wrong direction, see Figure 1 for a correct demonstration.


STREET WRAP™ FLEX WIDE (NON-RGB)

Flexible LED illumination

24
VDC





Accessories



Transparent PC clips*
A-TDMH-CLPL

* Transparent clips are not warranted if used in outdoor applications.



8-ft Aluminum track
A-TD-TRAL-8




End Caps*



Silicone end cap
A-TDHW-ECSI

* End cap quantities are available upon request.



Silicone insert, single color
X-C-TD-SI1C

Silicone insert, RGB
X-C-TD-SI3C



Silicone glue
A-SWFX-SA

Wiring

Single color product

