

TAP OUT™

# HANLEY ONE STIK

High-performance 24V LED illumination  
for new & retrofit sign cabinet applications

24  
VDC

TAP  
OUT →

## Specifications

**Dimensions L x W x H** ..... Single-sided.....See table x TBD x TBD  
 Double-sided.....See table x TBD x TBD

**Beam angle** .....170°

**Color temperature** .....7000 K

**Mounting options** ..... Socket (retro) / Brackets (new)

**Operating temp.** .....-40° C to +60° C

**Environment** ..... IP67

**Wire color** ..... White (+) / Gray (-)

**Packaging** ..... Single-sided..... 24 pieces per tube for 48"≤  
 12 pieces per tube for 120"≤  
 Double-sided..... 16 pieces per tube for 48"≤  
 8 pieces per tube for 120"≤

**Warranty** ..... 8-Year Product / 5-year Limited Labor



## Product Options

	Nominal length	Length	SKU	No. of mods	Lumens per Stik	Lumens/ft	Power	Max. units (96 W)	Case qty	UL number
SINGLE-SIDED	18"	15.91"	B-H1-S03-01870	3	420	317	2.85	33	24	PL-HL24-ON-P/ST-S-18
	24"	21.91"	B-H1-S04-02470	4	560	307	3.80	25	24	PL-HL24-ON-P/ST-S-24
	30"	27.91"	B-H1-S06-03070	6	840	361	5.70	16	24	PL-HL24-ON-P/ST-S-30
	36"	33.91"	B-H1-S07-03670	7	980	347	6.65	14	24	PL-HL24-ON-P/ST-S-36
	42"	39.91"	B-H1-S08-04270	8	1120	337	7.60	12	24	PL-HL24-ON-P/ST-S-42
	48"	45.91"	B-H1-S09-04870	9	1260	329	8.55	11	24	PL-HL24-ON-P/ST-S-48
	60"	57.91"	B-H1-S11-06070	11	1540	319	10.45	9	12	PL-HL24-ON-P/ST-S-60
	64"	61.91"	B-H1-S12-06470	12	1680	326	11.40	8	12	PL-HL24-ON-P/ST-S-64
	72"	69.91"	B-H1-S13-07270	13	1820	312	12.35	7	12	PL-HL24-ON-P/ST-S-72
	84"	81.91"	B-H1-S16-08470	16	2240	328	15.20	6	12	PL-HL24-ON-P/ST-S-84
	96"	93.91"	B-H1-S18-09670	18	2520	322	17.10	5	12	PL-HL24-ON-P/ST-S-96
	108"	105.91"	B-H1-S20-10870	20	2800	317	19.00	5	12	PL-HL24-ON-P/ST-S-108
	117"	114.91"	B-H1-S21-11770	21	2940	307	19.95	4	12	PL-HL24-ON-P/ST-S-117
	120"	117.91"	B-H1-S22-12070	22	3080	313	20.90	4	12	PL-HL24-ON-P/ST-S-120
DOUBLE-SIDED	18"	15.91"	B-H1-D06-01870	6	840	634	5.70	16	16	PL-HL24-ON-P/ST-D-18
	24"	21.91"	B-H1-D08-02470	8	1120	613	7.60	12	16	PL-HL24-ON-P/ST-D-24
	30"	27.91"	B-H1-D12-03070	12	1680	722	11.40	8	16	PL-HL24-ON-P/ST-D-30
	36"	33.91"	B-H1-D14-03670	14	1960	694	13.30	7	16	PL-HL24-ON-P/ST-D-36
	42"	39.91"	B-H1-D16-04270	16	2240	674	15.20	6	16	PL-HL24-ON-P/ST-D-42
	48"	45.91"	B-H1-D18-04870	18	2520	659	17.10	5	16	PL-HL24-ON-P/ST-D-48
	60"	57.91"	B-H1-D22-06070	22	3080	638	20.90	4	8	PL-HL24-ON-P/ST-D-60
	64"	61.91"	B-H1-D24-06470	24	3360	651	22.80	4	8	PL-HL24-ON-P/ST-D-64
	72"	69.91"	B-H1-D26-07270	26	3640	625	24.70	3	8	PL-HL24-ON-P/ST-D-72
	84"	81.91"	B-H1-D32-08470	32	4480	656	30.40	3	8	PL-HL24-ON-P/ST-D-84
	96"	93.91"	B-H1-D36-09670	36	5040	644	34.20	2	8	PL-HL24-ON-P/ST-D-96
	108"	105.91"	B-H1-D40-10870	40	5600	635	38.00	2	8	PL-HL24-ON-P/ST-D-108
	117"	114.91"	B-H1-D42-11770	42	5880	614	39.90	2	8	PL-HL24-ON-P/ST-D-117
	120"	117.91"	B-H1-D44-12070	44	6160	627	41.80	2	8	PL-HL24-ON-P/ST-D-120

Specifications subject to change without notice.

TAP OUT™

# HANLEY ONE STIK

**24**  
VDC

TAP  
OUT →

*High-performance 24V LED illumination  
for new & retrofit sign cabinet applications*

## Recommended Coverage Chart (Cabinets)

Depth from stik to face	Maximum spacing between stiks
5"	10"
6"	14"
7"	16"
8"+	18"

Product and depth may vary depending on face material and desired brightness.

All spacing guidelines in this chart were done using 7328 White Acrylic faces. Other materials, thicknesses, and color can affect these guidelines in your sign. To ensure accuracy, it is recommended that you test the product in your specific application in a dark setting prior to installation. If you have concerns or questions about the materials you are using for your application please contact us for assistance.



🌐 [principalsloan.com](http://principalsloan.com)

📞 325.227.4577

📍 3490 Venture Dr., San Angelo, TX 76905

© 2025 Principal Industries Rev B 2025-02-18

