



Tap Out™ Stik 24V

Closing the price gap between LEDs and fluorescents!

SPECIFICATIONS

Beam Angle	160° Low Dome, Batwing Optic	
Certifications	UL & cUL Recognized (SAM Manual), CE, RoHs	
Dimensions	Single-Sided	.71"W x .75"H x Length
	Double-Sided	.71"W x 1.1"H x Length
Efficacy	105 LM/W	
CCT/Wavelength	True White	7000K
Fastening	Socket (retro) / Brackets (new)	
Input	24VDC	
Max Mods (Series)	N/A	
Operating Temp	-40° to +60°C	
Packaging	Single-Sided	24 pieces per box
	Double-Sided	16 pieces per box
Power Supply	P-LED 24VDC	
Protection Grade	IP67	
Warranty	10-Year Product / 5-Year Limited Labor	

This product is covered by issued U.S. Patent No. 9,851,054 and 10,024,501.

FEATURES

- NOT field cuttable
- For use in cabinet signs
- Best dollar per lumen value on the market
- All Tap Out™ Stiks come with preassembled whips for easy installation
- Comes in standard color temperature
- Batwing optic lens for even illumination at all cabinet depths (12"-30" Double-Sided)
- Standard T-12 lengths available (18"-120")
- Two mounting options:
 - Fits into existing sockets for retros
 - New construction Mounting Brackets

WIRING DETAILS


White Solid	Positive
White/Black Stripe	Negative

RECOMMENDED COVERAGE CHART

Depth from Stik to Face	Estimated Spacing between Stiks
5"	10"
6"	12"
7" – 8"	16"
9" – 12"	18"

>12 (Use two banks Single-Sided)


Note: Product and depth may vary depending on face material and desired brightness.



Reduce ROI Time



Increase Profits



10-YEAR WARRANTY



Tap Out Stik 24V Single-Sided™

PRODUCT OPTIONS

T-12	Actual Length	Lumens per Stik	No. of Mods	Watts	Max. Units (96W)	Whips	UL Part Number*	SKU
18"	15.91"	556	4	5.28	18	1-3 ft.	PL-OP2-TO3-P/ST-SS-18-TW24	B-TO-S04-01870-24
24"	21.91"	556	4	5.28	18	1-3 ft.	PL-OP2-TO3-P/ST-SS-24-TW24	B-TO-S04-02470-24
30"	27.91"	834	6	7.92	12	1-3 ft.	PL-OP2-TO3-P/ST-SS-30-TW24	B-TO-S06-03070-24
36"	33.91"	1,112	8	10.56	9	1-3 ft.	PL-OP2-TO3-P/ST-SS-36-TW24	B-TO-S07-03670-24
42"	39.91"	1,112	8	10.56	9	1-3 ft.	PL-OP2-TO3-P/ST-SS-42-TW24	B-TO-S08-04270-24
48"	45.91"	1,390	10	13.20	8	1-3 ft.	PL-OP2-TO3-P/ST-SS-48-TW24	B-TO-S09-04870-24
60"	57.91"	1,668	12	15.84	6	1-3 ft.	PL-OP2-TO3-P/ST-SS-60-TW24	B-TO-S012-06070-24
64"	61.91"	1,668	12	15.84	6	1-3 ft.	PL-OP2-TO3-P/ST-SS-64-TW24	B-TO-S012-06470-24
72"	69.91"	1,946	14	18.48	5	1-6 ft.	PL-OP2-TO3-P/ST-SS-72-TW24	B-TO-S013-07270-24
84"	81.91"	2,224	16	21.12	4	1-6 ft.	PL-OP2-TO3-P/ST-SS-84-TW24	B-TO-S016-08470-24
96"	93.91"	2,502	18	23.76	4	1-6 ft.	PL-OP2-TO3-P/ST-SS-96-TW24	B-TO-S018-09670-24
108"	105.91"	2,780	20	26.4	3	1-6 ft.	PL-OP2-TO3-P/ST-SS-108-TW24	B-TO-S020-10870-24
117"	114.91"	3,058	22	29.04	3	1-6 ft.	PL-OP2-TO3-P/ST-SS-117-TW24	B-TO-S021-11770-24
120"	117.91"	3,058	22	29.04	3	1-6 ft.	PL-OP2-TO3-P/ST-SS-120-TW24	B-TO-S022-12070-24

Tap Out Stik 24V Double-Sided™

PRODUCT OPTIONS


T-12	Actual Length	Lumens per Stik	No. of Mods	Watts	Max. Units (96W)	Whips	UL Part Number*	SKU
18"	15.91"	1,112	8	10.56	9	1-3 ft.	PL-OP2-TO3-P/ST-DS-18-TW24	B-TO-D08-01870-24
24"	21.91"	1,112	8	10.56	9	1-3 ft.	PL-OP2-TO3-P/ST-DS-24-TW24	B-TO-D08-02470-24
30"	27.91"	1,668	12	15.84	6	1-3 ft.	PL-OP2-TO3-P/ST-DS-30-TW24	B-TO-D12-03070-24
36"	33.91"	1,946	14	18.48	5	1-3 ft.	PL-OP2-TO3-P/ST-DS-36-TW24	B-TO-D14-03670-24
42"	39.91"	2,224	16	21.12	4	1-3 ft.	PL-OP2-TO3-P/ST-DS-42-TW24	B-TO-D16-04270-24
48"	45.91"	2,502	18	23.76	4	1-3 ft.	PL-OP2-TO3-P/ST-DS-48-TW24	B-TO-D18-04870-24
60"	57.91"	3,336	24	31.68	3	1-3 ft.	PL-OP2-TO3-P/ST-DS-60-TW24	B-TO-D24-06070-24
64"	61.91"	3,336	24	31.68	3	1-3 ft.	PL-OP2-TO3-P/ST-DS-64-TW24	B-TO-D24-06470-24
72"	69.91"	3,614	26	34.32	2	1-6 ft.	PL-OP2-TO3-P/ST-DS-72-TW24	B-TO-D26-07270-24
84"	81.91"	4,448	32	42.24	2	1-6 ft.	PL-OP2-TO3-P/ST-DS-84-TW24	B-TO-D32-08470-24
96"	93.91"	5,004	36	47.52	2	1-6 ft.	PL-OP2-TO3-P/ST-DS-96-TW24	B-TO-D36-09670-24
108"	105.91"	5,560	40	52.80	1	1-6 ft.	PL-OP2-TO3-P/ST-DS-108-TW24	B-TO-D40-10870-24
117"	114.91"	5,838	42	55.44	1	1-6 ft.	PL-OP2-TO3-P/ST-DS-117-TW24	B-TO-D42-11770-24
120"	117.91"	6,116	44	58.08	1	1-6 ft.	PL-OP2-TO3-P/ST-DS-120-TW24	B-TO-D44-12070-24

*TW = True White (7000K)

This product is covered by issued U.S. Patent No. 9,851,054 and 10,024,501.

TAP OUT STIK

Do Not Mix With Previous Version.



p-led.com | 325.227.4577 | sales@p-led.com

TAP OUT STIK 24V